ACCESSORIES AND MOUNTING AIDS







INSTALLATION AIDS for self-levelling manhole covers

PKDY formwork carrier

Carrier for installing formwork in the asphalt layer when installing self-levelling frames.

Universal for all KASI self-levelling frames.

It is used for installation during hatch replacement and for preparation of the installation before the finisher.

HATCH for temporary operation

IIAZAK

Cast iron manhole cover used to cover manholes during temporary operation within construction.

It is particularly important as a replacement for self-levelling frames that cannot be temporarily used without being fully built in.

The hatch is manufactured under load class C250.

It is mounted directly into the cone or buffer ring.



PKDM formwork

Formwork for selflevelling standard series frame without hinge and trap pockets.

PKDM8 formwork

Formwork for Europa 8 and 9 self-levelling frames with hinge, without trap pockets.

PKDN formwork

Formwork for selflevelling standard series frame without hinge, with trap pockets.

PKDN8 formwork

Formwork for Europa 8 and 9 self-levelling frame with hinge and trap pockets.







KEYS for opening hatches and grilles

XPUK universal key for KASI hatches

XPK-RD key for control system lock

HANDLING HOOKS

SHZPK manual lifting hook short

SHZPD manual lifting hook long

AUXILIARY PARTS for self-levelling frames

LDRNN

adapter for attaching DN600 self-levelling frame

LFRNN

adapter for attaching DN600 LFRF/LFRE self-levelling frame

L8ERNNC

adapter for attaching DN800 self-levelling frame



ACCESSORIES FOR PRODUCTS





HANDLING PLIERS

SV15UNI self-clamping universal handling pliers 1.5 t SV25UNI

self-locking universal handling pliers 2.5 t

SUSPENDED HANDLING

HUK025 universal ball coupling 1.5-2.5 t

HLZM16 rope suspension M16, load capacity: 1.2 t

HP2.5M65 KK-mag container transport handle 2.5 t ø 65 mm

HP2.5M100 KK-mag container transport handle. 2.5 t, 100 mm



DAMPING INSERTS

XT8 EPDM damping insert for Europa 8

XTD EPDM shock absorbing insert for Standard frame

XTDPUR

PUR shock absorbing insert for Standard frame



TPS

assembly foam for joining street gullies



Training focused on hatch installation problems

We will be happy to visit you or welcome you to our facility in order to train you on how to properly install KASI hatches.

We will discuss various installation procedures, including the use of special fixtures and appropriate construction materials. We will answer any practical questions you may have about our hatches. We will explain what to use and how to use it so that our hatches work to everyone's satisfaction after installation.

Installation by additional milling

What do we think is the ideal way to install hatches? Only if the hatch is not used at all during the preparation of all layers. The construction company will save time avoiding the hatch and all construction layers will be homogeneously compacted. The cover is fit to the finished roadway, in the exact plane, with a full guarantee of no damage during temporary use.

We cooperate with specialists in the field of hatchinstallation

Just like the products themselves, the technology for incorporating them is continuously moving forward.

We work closely with companies where hatch installation is a daily routine. Therefore, we have practical experience from construction sites, directly from professionals. We can also arrange training or demonstrations of all installation types directly from these specialists.



Would you like more information? Contact our engineers:

Petr Novotný +420 606 685 239 Petr Trnka

+420 606 202 012

petr.novotny@kasi.cz

trnka@kasi.cz

KASI spol. s r. o., Chrudimská 1602, Přelouč 535 01, Czech Republic, phone: +420 466 501 755, e-mail: obchod@kasi.cz, www.kasi.cz